



United Technologies



PRODUCT LINE-UP

Residential air conditioners



Carrier air conditioning

Energy savings

Maximum energy savings thanks to accurate digital power control and super-efficient compressor.

Comfort

Provides consistent comfort by quickly generating and evenly maintaining the desired room temperature.

Quiet operation

Extremely quiet indoor unit using DC brushless motor and air flow design.





United Technologies



The inside of the indoor unit is kept dry to prevent mold from forming.

Self clean



Louver positioning memory

When you start your unit again after shutting down, its louver will restore to the angle originally set by you.



Hidden display

The light can be turned off by a remote control when the unit is running..





Remote Control

You can control all the functions of the unit with this intuitive remote control



Follow me

When pressing the "Follow me" button, the room temperature will be based on the temperature around your remote controller.



Timer

Use the timer function to experience the most comfortable climate whenever you want.





Silence mode

When you select “silence” on your remote control, the indoor fan will run on the super breeze mode, which keeps your environment comfortable.

Advanced Inverter Technology

The high efficiency of Carrier's inverter comes from the latest DC Rotary inverter technology. The result is non-intrusive, world-class performance in energy saving and comfort.





After power failure unit will restart automatically in the same mode as prior to the power failure.

Auto Restart



When your air conditioner detects refrigerant leakage it will automatically stop the unit and generate a dedicated code for safety.

Refrigerant Leak Detection

1W Standby

This intelligent on-off technology enables your Carrier product to minimize energy consumption during standby mode.





SPECIFICATION OF QHF HIGH WALL

INDOOR TYPE		42QHF009DS(G)	42QHF012DS(G)	42QHF018DS(G)	42QHF022DS(G)
OUTDOOR TYPE		38QUS009DS(N)	38QUS012DS(N)	38QUS018DS(N)	38QUS022DS(N)
Cool capacity	kW	2.7 (1.0-3.2)	3.5 (1.0-3.6)	5.1 (1.5-5.3)	6.4 (1.7-6.6)
Heating capacity	kW	2.9 (1.0-3.5)	3.8 (1.0-4.1)	5.2 (1.3-5.6)	6.4 (1.5-6.8)
Heating capacity at -7 °C	kW	2.7	3.2	3.8	4.3
Heating capacity at -10 °C	kW	2.5	3.1	3.5	4.2
Heating capacity at -15 °C	kW	2.2	2.7	3.1	4.1
P design capacity cooling	kW	2.7	3.5	5.1	6.4
P design capacity heating (average)	kW	2.2	2.8	4.2	5.2
P design capacity heating (warmer)	kW	2.3	3.0	4.5	5.6
Temp range cooling	°C	-10~46	-10~46	-10~46	-10~46
Temp range heating	°C	-15~24	-15~24	-15~24	-15~24
SEER / SCOP (average) / SCOP (warmer)	W/W	6.1 / 4.0 / 5.2	6.1 / 4.0 / 5.0	6.2 / 4.0 / 5.0	6.2 / 4.0 / 4.7
Energy label		A++ / A+ / A+++	A++ / A+ / A++	A++ / A+ / A++	A++ / A+ / A++
Yearly energy consumption	kWh	155 / 770 / 619	201 / 980 / 840	288 / 1470 / 1260	361 / 1820 / 1668
EER/COP	W/W	3.3 / 3.8	2.9 / 3.1	2.9 / 3.3	2.9 / 3.1
Voltage / Hz		230V / 50Hz	230V / 50Hz	230V / 50Hz	230V / 50Hz
Standard current (cooling)	A	3.7	5.5	8.1	9.9
Standard input (cooling)	W	810	1210	1760	2200
Standard current (heating)	A	3.5	5.7	7.3	9.2
Standard input (heating)	W	760	1250	1600	2050
Rated current	A	9.5	9.5	12.5	13.0
Rated input	W	2100	2100	2750	2950



INDOOR UNIT		42QHF009DS(G)	42QHF012DS(G)	42QHF018DS(G)	42QHF022DS(G)
Sound power level	dB(A)	57	58	59	63
Sound pressure level (high/med/low/silence)	dB(A)	42/38/34/22	44/40/36/23	45/41/38/24	50/48/43/29
Air flow (high/med/low/silence)	m3/h	470/390/300/180	500/390/300/180	600/500/400/260	900/820/700/450
Weight (Net/Gross)	kg	7.5 / 10.5	7.5 / 10.5	9.5 / 13.0	12.5 / 17.5
Dimensions (WxDxH)	mm	800x188x275	800x188x275	940x205x275	1045x235x315
OUTDOOR UNIT		38QUS009DS(N)	38QUS012DS(N)	38QUS018DS(N)	38QUS022DS(N)
Sound power level	dB(A)	61	62	63	68
Sound pressure level	dB(A)	53	54	55	58
Airflow	m3/h	1800	2000	2000	2500
Weight (Net/Gross)	kg	27.5 / 29.5	30.5 / 33.0	37.0 / 40.0	47.0 / 50.0
Dimensions (WxDxH)	mm	780x250x540	810x310x 558	810x310x558	845x320x700
PIPING					
Refrigerant amount	kg	0.80	1.03	1.70	1.95
Liquid side/ Gas side	mm(inch)	6.35/9.52 (1/4"/3/8")	6.35/9.52 (1/4"/3/8")	6.35/12.7 (1/4"/1/2")	9.52/15.9 (3/8"/5/8")
Standard piping length	m	5	5	5	5
Min piping length	m	3	3	3	3
Max piping length	m	20	20	25	25
Max difference	m	8	8	10	10
Additional charge	g/m	15	15	15	30

Note

* Model number	Indoor	Outdoor	Remark
Western Europe	42QHFxxxDS	38QUSxxxDS	this is standard
Germany	42QHFxxxDSG	38QUSxxxDS	added 1 digit " G" for ID
Nordic Version	42QHFxxxDS	38QUSxxxDSN	added 1 digit " N" for OD

* Sound data @ cooling mode

SPECIFICATION OF QHF HIGH WALL

For further information please visit www.carrier-beijerref.com

BEIJER REF